



Cummins is one of world top famous engines and widely acceptable all over the world. Cummins INC is a global power leader, a corporation of complementary business units that design, manufacture, distribute and service engines and related technologies, including fuel systems, controls, air handling, filtration, emission solutions and electrical power generating systems. Headquartered in Columbus, Indiana, (USA) Cummins serves customers in approximately 190 countries and territories through a network of more than 600 company-owned and independent distributor locations and approximately 5,200 dealer locations.

As one of the biggest Cummins OEM partners in China, Ettes Power Cummins diesel genset are ranging from 25kVa up to 1650kVa, driven by engines series of 4B3.9, 6B5.9, 6C8.3, 6L8.9, QSZ13, N855, M11, K19, QSK19-G4, QSK19-G5, K38 and K50. Cummins diesel generators are vastly used in transportation sector, buildings, telecom, schools, hospitals, ships, petroleum oil fields and industrial power supplying area etc, which can be applied as main power or emergency generator. With Cummins engine's reliability, durability, flexibility, energy-saving and worldwide after-service networks, Cummins gensets act as a fundamental role in global generators industry.



Cummins Series Diesel Generator Set (60Hz,1800RPM)											
Genset Model	Prime Power		Standby Power		Engine Model	Max Engine Power	Bore×Stroke	Alternator	No. of Cylinders & Type	Overall dimension (L*W*H)(mm)	Weight (kg)
	kW	kVa	kW	kVa	CUMMINS	kW	(mm)	Stamford, SMF or Equal			
EC-30	22	28	24	30	4B3.9-G	33	102×120	BCI Series	4.L	1820*760*1280	876
EC-33	24	30	26	33	4B3.9-G	33	102×120	BCI Series	4.L	1820*760*1280	888
EC-41	30	38	33	41	4BT3.9-G	44	102×120	BCI Series	4.L	1820*760*1400	890
EC-50	36	45	40	50	4BT3.9-G	44	102×120	BCI Series	4.L	1820*760*1400	893
EC-69	50	63	55	69	4BTA3.9-G	66	102×120	UCI Series	4.L	2000*760*1450	930
EC-83	60	75	66	83	4BTA3.9-G	74	102×120	UCI Series	4.L	2000*760*1450	930
EC-88	64	80	70	88	4BTA3.9-G11	90	102×120	UCI Series	4.L	2000*760*1450	930
EC-100	72	90	80	100	4BTA3.9-G11	90	102×120	UCI Series	4.L	2000*760*1450	930
EC-110	80	100	88	110	6BT5.9-G	110	102×120	UCI Series	6.L	2230*830*1490	1450
EC-125	90	113	100	125	6BT5.9-G	110	102×120	UCI Series	6.L	2230*830*1490	1520
EC-138	100	125	110	138	6BTA5.9-G	132	102×120	UCI Series	6.L	2300*850*1520	1590
EC-160	116	145	128	160	6BTAA5.9-G	145	102×120	UCI Series	6.L	2300*850*1520	1620
EC-188	135	170	150	188	6BTAA5.9-G12	165	102×120	UCI Series	6.L	2300*850*1520	1620
EC-220	160	200	176	220	6CTA8.3-G	190	114×135	UCI Series	6.L	2480*880*1650	1850
EC-250	180	225	200	250	6CTAA8.3-G	220	114×135	UCI Series	6.L	2540*980*1650	2050
EC-275	200	250	220	275	6LTAA8.9-G	258	140×152	UCI Series	6.L	2540*980*1670	2200
EC-285	212	265	228	285	6LTAA8.9-G	258	140×152	UCI Series	6.L	2540*980*1670	2200
★EC-275B	N/A	N/A	220	275	NT855-GA	257	114×135	UCI Series	6.L	3300*1150*1700	2600
EC-300	220	275	240	300	6LTAA8.9-G	265	114×135	UCI Series	6.L	2540*980*1670	2200
EC-350	250	313	280	350	NTA855-G1	317	114×135	UCI Series	6.L	3300*1150*1700	2600
EC-385-1	280	350	308	385	NTA855-G1B	347	140×152	HCI Series	6.L	3300*1150*1700	2680
EC-385-2	280	350	308	385	NTA855-G2	347	140×152	HCI Series	6.L	3300*1150*1700	2690
• EC-413-1	300	375	330	413	6ZTAA13-G3	380	130×160	HCI444FS	6.L	3300*1250*1900	3100
EC-413-2	300	375	330	413	NTA855-G3	399	140×152	HCI Series	6.L	3300*1150*1700	2700

EC-440	320	400	352	440	NTA855-G3	399	140×152	HCI Series	6.L	3300*1150*1700	2720
• EC-450P	360	450	N/A	N/A	6ZTAA13-G4	400 Prime	130×160	HCI544C	6.L	3300*1250*1900	3100
EC-480	350	438	385	480	6ZTAA13-G2	415	130×160	HCI544C	6.L	3300*1250*1900	3100
EC-500-1	360	450	400	500	KTA19-G2	448	159×159	HCI Series	6.L	3400*1258*2050	3400
• EC-500-2	360	450	400	500	QSZ13-G2	440	130×163	HCI Series	6.L	3300*1250*1900	3400
• EC-550	400	500	440	550	QSZ13-G3	500	130×163	HCI544D	6.L	3300*1250*1900	3300
EC-562	410	513	450	562	KTA19-G3	511	159×159	HCI Series	6.L	3400*1258*2050	3400
EC-625-1	450	563	500	625	KTA19-G3A	563	159×159	HCI Series	6.L	3400*1258*2050	4000
EC-625-2	450	563	500	625	KTA19-G4	563	159×159	HCI Series	6.L	3400*1258*2050	4600
EC-688	480	600	550	688	KTAA19-G5	605	159×159	HCI Series	6.L	3650*1638*2050	4900
• EC-713	500	625	570	713	QSK19-G4	634	159×159	HCI Series	6.L	3650*1638*2050	5300
• EC-750	550	688	600	750	QSK19-G5	669	130×163	HCI Series	6.L	3650*1638*2050	5300
★EC-750B	N/A	N/A	600	750	KTAA19-G6A	664	159×159	HCI Series	6.L	3650*1638*2050	5000
EC-850	620	775	680	850	KT38-G	746	159×159	HCI Series	12.Vee	4500*2060*2430	6850
EC-963	700	875	770	963	KTA38-G1	847	159×159	LVI Series	12.Vee	4500*2060*2430	6980
EC-1000	720	900	800	1000	KTA38-G2	895	159×159	LVI Series	12.Vee	4500*2060*2430	6980
EC-1038	750	938	830	1038	KTA38-G2B	920	159×159	LVI Series	12.Vee	4500*2060*2430	7200
EC-1100	800	1000	880	1100	KTA38-G2A	1007	159×159	LVI Series	12.Vee	4500*2060*2430	7390
EC-1250	900	1125	1000	1250	KTA38-G4	1112	159×159	LVI Series	12.Vee	4800*2060*2430	7900
★EC-1375	N/A	N/A	1100	1375	KTA38-G9	1220	159×159	LVI Series	12.Vee	4600*2100*2430	8600
• EC-1438	960	1200	1150	1438	QSK38-G5	1279	159×159	LVI Series	12.Vee	4800*2060*2430	8000
EC-1512	1100	1375	1210	1512	KTA50-G3	1380	159×159	PI Series	16.Vee	5000*2200*2500	10300
EC-1875	1250	1562	1500	1875	KTA50-G9	1656	159×159	PI Series	16.Vee	5220*2200*2565	11400

Remarks:

- ◆ Above gensets are based on 60Hz, 1800RPM, 3 Phases & 4 Wires, Power Factor 0.8.
- ◆ Engine Model with “ • ” means with EFI (Electrical Fuel Injection) system.
- ◆ Genset Model with “★” means it is for standby power.
- ◆ Standard voltage is 480/270V, other low voltages and high voltages are available.
- ◆ Special demands for Soundproof Canopy, ATS, Parallel Control and Remote Control are available.
- ◆ The data herein can vary depending on individual production requirements or due to improved technology.



ETTES POWER MACHINERY CO LTD

The Key Supplier for Complete Power Generating Systems

Tel: +86-22-23796980

E-mail: info@ettespower.com

Fax: +86-22-23796811

Internet: www.ettespower.com

