

## Superior Engine Generation **Drive a Better World**



Ettes Power is the leading manufacturer and supplier for diesel & gas generators from 20kW upto 4500kW. We use world top engines (Cummins, MAN, CAT-MWM, CNPC 190 Series and Low speed 300 Series etc.) to ASSEMBLE into complete-generator-set and CHP units. Ettes gensets enjoy hot markets in more than 70 countries all over the world including Latin America, Africa, Middle East, Europe and Asia markets.

190 Series gas engines are developed by cooperation with AVL from Germany and Austria. The engine assembling plant is affiliated to CNPC (China National Petroleum & Oil Corporation), those engines work extensively in 90% of China oil fields and coal mines, and enjoy hot markets in global.

Benefits of ETTES-CNPC 190 Series gas engines & Genset

- The engine performance is "Leading China" and "First class Global"
- Long history: produced by engines plant under control by CNPC (China National Petroleum & Oil Corporation), it is the first and the largest engine manufacture in China since 1953.
- Proven Technology: widely used in 90% of China Oil & Gas Fields, Coalmines, Vessels and other areas under severe working conditions.
- Fuel flexibility: designed for operation on a wide range of methane based gases including natural gas, biogas, oilfield gas, coal mine methane and ٠ shale gas and other special gas.
- Designed for intensive use (continuous duty)
- Capable of working with variable loads. ٠
- Advanced technology of close-loop control, lean-burn and Mixing before turbo. ٠
- Adopting highly intelligent gas control system of Woodward EGS or Motortech, the air fuel ratio can be automatically adjusted as per fluctuation of ٠ gas components.
- Adopting intelligent & digital ignition system from Motortech or Altronic.
- Adopting super-turbocharged technology from ABB. ٠
- ٠ Heat Recovery system to realize CHP, Cogeneration and Distribution Energy.
- Integrated & modularized unit to facilitate easy transport and quick setup. ٠
- Easy Maintenance in Low Cost. ٠
- Ensured annually continuous working over 8000 hours.
- Longer life span of 15~20 years. ٠



	Genset Model	EJ-1000NB		
Gas Gen-Set	Rated Power (kW/kVa)	1000/1250		
	Manufacturer/Assembler	ETTES POWER		
	Gas Engine Manufacture	CNPC ENGINES ASSEMBLING PLANT		
	Gas Engine Model	H16V190ZLT		
	Engine Rated Power (kW/hp)	1200/1632 (1000rpm); 1440/1930 (1200rpm)		
	Applicable Fuel	Methane Base Gas: Natural Gas, Biogas, Oilfield Gas, Landfill G		
	Applicable Fuel	Sewage Gas, Coalmine Bed Gas and Shale Gas etc.		
		Advanced close loop electrically controlled;		
	Typical Features	Lean Burn Technology;		
		Mixing Before Turbocharger;		
	Type	Water Cooled, Four Stroke, Spark Ignition, Turbocharger and		
	Туре	after-cooled, Outer Mixing		
	Cooling Method	Standard: Open Cooling System by Heat Exchanger + Cooling To		
		Optional: Closed Water Cooling by Fan Radiator		
	Starting Method	24VDC Electrical		
	Bore × Stroke (mm)	190×215		
Coo Fraina	Displacement (L)	97.53		
Gas Engine	Compression Ratio	11:1		
	Average Speed of Piston (m/s)	10.5		
	Cylinder numbers and Type	16.Vee, 60° Angle		
	Governor/Actuator	Woodward or Heinzmann or Motortech		
	Ignition System	Motortech or Altronic or Equivalent		
	Air-Fuel Control	EGS Automatic A/F Control		
	Rated Speed (r/min)	1000 (50Hz) / 1200(60Hz)		
	Idle Speed (RPM)	700		
	Direction of Rotation	Counter-clockwise		
	Oil Consumption (g/kW.h)	≤0.8		
	Lube Oil Capacity (L)	460		
	Heat Consumption(kJ/kW.h)	≤9500		
	Exhaust Gas Temperature	≤550°C		
	Intake Gas Pressure Required (kPa)	10~20 (biogas) / 100~400 (natural gas)		
	Noise Level (Db)	≤110 (without silencer and soundproof container)		

-				
		_		
	-			

			Alternator Brar	nd	Siemens or Equivalent				
		Alternator Mod	el	1FC6 Series					
			Frequency (Hz	)	50/60				
CIENTEN	C				400	0/230(50Hz), 480/2	70(60Hz)		
SIEMEN	2	Rated Voltage (V)		∨)	Other Special Low Voltages and				
					High Voltage of 6.3kV, 6.6kV, 10.5kV, 13.8kV are available				
Alternator			Power Factor (Co	sφ)	0.8				
			Туре		Insulation Class IP23, Protection Class H				
			Excitation Meth	od	Self-excited, Brushless				
Voltage Regulation				AVR					
		Standard Control System: advanced SIVAC control panel by Siemens Technology, adopting control module o							
		ComAp Intelilite Series, with functions including manual keys, alarms, protections, auto start and shut down							
Control System		showing running parameters in LCD Display.							
		Engine SCADA System, Communications protocol RS485							
		<b>Options:</b> Auto parallel synchronization control panel, Remote control system etc.							
		Net Weight (KG)			22000				
Size and Weight		Dimension (L×W×H, mm)			6070×2380×2776 (based on open cooling system)			tem)	
			Main Ele	ctronic Performan	ce Data				
Voltage				Frequency					
Ctabilita d Danulatia	Instanta	aneous	<b>F</b> hustustia	Stabilized	Instantaneous	Recovery	Elucture tiere		
Stabilized Regulation	regula	tion	Recovery Time	Fluctuation	Regulation	regulation	Time	Fluctuation	
≤ ±2%	≤ ±5	5%	<b>1</b> s	≤ 0.5%	≤ 0.5%	≤ ±10%	<5s	≤ 0.5%	

★ Above values are provided for information purpose only and are non-binding. The data given in official offer is decisive.





Knowing it is Ettes Power-The Key Supplier for Complete Power Generating System-

 Website:
 www.ettespower.com
 Tel:+86-2223796980
 Fax: +86-2223796811
 Email: info@ettespower.com

Docs Version March 2016